

IGS-PL-010(0) : Part 5

2006

81



National Iranian Gas Co.

مدیریت پژوهش و فناوری

Research and Technology Management

امور تدوین استانداردها

Standardization Division

IGS

Iranian Gas Standards

Specification for :

مشخصات فنی :

**Ball Valves, Flanged Ends, Class Rating :150,300,600
size : 1/2 to 1,1/2 in.**

APPROVED

پیشگفتار

- ۱- این استاندارد/دستورالعمل بمنظور استفاده اختصاصی در شرکت ملی گاز ایران و شرکتهای فرعی وابسته تهیه شده است.
- ۲- شرکت ملی گاز ایران در مورد نیازهای عمومی از استانداردهای وزارت نفت (IPS) و در مورد نیازهای اختصاصی از استانداردهای اختصاصی خود (IGS) استفاده می نماید.
- ۳- استانداردهای شرکت ملی گاز ایران (IGS) توسط کمیته های تخصصی استاندارد متشکل از کارشناسان بخش های مختلف و یا مشاور تهیه می شود و توسط شورای استاندارد (منتخب هیئت مدیره شرکت ملی گاز ایران) به تصویب میرسند.
- ۴- در تنظیم متن استانداردهای (IGS) از کلیه منابع شناخته شده استاندارد، اطلاعات فنی - تخصصی مربوط به صنایع گاز دنیا، مشخصات فنی تولیدات سازندگان معتبر جهانی و نیز از نتیجه تحقیقات و تجربیات کارشناسان و متخصصان داخلی بر حسب مورد استفاده می شود. همچنین بمنظور استفاده هر چه بیشتر از تولیدات داخلی قابلیت های سازندگان داخلی نیز مورد توجه قرار میگیرد.
- ۵- استانداردها از طریق پایگاه اینترنتی شرکت * و یالوح فشرده (CD) در اختیار واحدها و کاربران قرار می گیرد .
- ۶- استانداردها بطور متوسط هر ۵ سال یکبار و یادر صورت ضرورت زودتر، مورد بازنگری و بروزرسانی قرار میگیرند. بنابراین کاربران باید همیشه آخرین نگارش را مورد استفاده قرار دهند.
- ۷- هرگونه نظر و یا پیشنهاد اصلاح در مورد استانداردها مورد استقبال و بررسی قرار خواهد گرفت و در صورت تأیید، استاندارد مربوطه نیز مورد تجدیدنظر قرار خواهد گرفت .

تعاریف عمومی

در متن استانداردهای (IGS) از تعاریف و اصطلاحات زیر استفاده میشود.

- ۱- "شرکت" (COMPANY): منظور از شرکت "شرکت ملی گاز ایران" و یا شرکتهای فرعی وابسته میباشد.
- ۲- "فروشنده" (SUPPLIER/VENDOR): به فرد یا موسسه ای اطلاق میگردد که تعهدی رانسبت به شرکت تقبل نموده است.
- ۳- "خریدار" (PURCHASER): منظور از خریدار "شرکت ملی گاز ایران" و یا شرکتهای فرعی وابسته میباشد.
- ۴- "SHALL": در مواردی بکاربرده میشود که انجام خواسته مورد نظر اجباری است
- ۵- "SHOULD": در مواردی بکاربرده میشود که انجام خواسته مورد نظر ترجیحی و درعین حال اختیاری است
- ۶- "MAY": در مواردی بکاربرده میشود که انجام کار به شکل مورد بحث نیز قابل قبول میباشد

FOREWORD

This standard is intended to be mainly used by **NIGC** and contractors and has been prepared on interpretation of recognized standards , technical documents , knowledge ,backgrounds and experiences in gas industries at national and international levels.

Iranian Gas Standards (**IGS**) are prepared , reviewed and ammended by technical standard committees within NIGC Standardization Div. and submitted to the **NIGC's "STANDARDS COUNCIL"** for approval .

IGS Standards are subject to revision , amendment or withdrawal , if required , thus the latest edition of **IGS** shall be checked/inquired by **NIGC** users .

This standard must not be modified or altered by the end users within **NIGC** and her contractors. Any deviation from normative references and/or well known manufacturers specifications must be reported to Standardization div.

Any comments from concerned parties on **NIGC** distributed **IGS** are welcome to technical standards committees and will receive serious attention and consideration should a revision to standards is recommended .

GENERAL DEFINITIONS :

Throughout this standard the following definitions , where applicable , should be followed :

1- "**STANDARDIZATION DIV.**" has been organized to deal with all aspects of industrial standards in NIGC . Therefore , all queries for clarification or amendments are requested to be directed to the mentioned div.

2- "**COMPANY** " : refers to national iranian gas company .

3- "**SUPLIER**" : refers to a firm who will supply the service , equipment or material to igs specification whether as the prime producer or manufacturer or a trading firm .

4- "**SHALL**" : is used where a provision is mandatory.

5- "**SHOULD**" : is used where a provision is advised only.

6- "**MAY**" : is used where a provision is completely discretionary.

Website : www.nigc.ir/igs

E-mail : nigcigs@nigc.org

SPECIFICATION OF BALL VALVES, FLANGED ENDS,

CLASSRATING : 150,300,600

SIZE RANGE : $\frac{1}{2}$ TO $1\frac{1}{2}$ IN

Ball valve, full bore , for gas distribution and transmission network, carbon steel , flanged ends, R.F, C.S.F , wrench operated, anti static design .

Stem shall be anti blow out type. Fire safe acc. To BS5146 part 1 or equivalent.

Suitable for max. service temp. of 50°C and ambient temp. of -29°C to +60°C.

All valves shall be furnished with a valve position indicator, on wrench or handwheel showing open position in the direction of flow.

The on / off marking shall be in English , easily visible and permanently legible .

Design, dimensions, testing, inspection and marking shall be all acc. To BS – EN- ISO 17292 , 2004.

The applicability of changes in codes and standards that occur after the date of this specification shall be mutually agreed upon by the purchaser and manufacturer.

MATERIALS:

Body, body connector & cover :

Forged carbon steel at least to astm A105 or to B.S. 1503 grade 221/550 or from bar stok acc. To B.S.970, part'1, grade 070 M20.

Ball & stem :

Forged carbon steel at least to ASTM A105 or B.S. 1503 grade 221/550.

Ball shall be hard chromium or electroless nickel plated, with final mirror finish preparation and min plating thickness of 25µm to ASTM B650 respectively.

Bolts and nuts:

Shall be acc to ASTM A193 B7/A194 2H

Non – metallic parts:

Shall be made of suitable elastomer fluorocarbon material (type and relevant standard shall be specified by manufacturer)

**Valve external surface shall be painted acc. To manufacturing standard
(technical details shall be provided by manufacturer)**

NOMINAL SIZE
(IN)

FACE TO FACE DIMENSION
CLASS RATING

N.S CLASS	150	300	600
1/2	108	140	165
3/4	117	152	190
1	127	165	216
1 $\frac{1}{4}$	140	178	229
1 $\frac{1}{2}$	165	190	241

Note :

- 1/ Require class rating shall be specified by purchaser.
- 2/ Flange class rating shall be matchable with valve class rating.